



XL-333 Liquid Extraction Detergent

SDS Number: S825

Revision Date: May 30, 2017

Page 1 of 5

PRODUCT AND COMPANY IDENTIFICATION

Product Name: Revision Date: Version: SDS Number:

1

XL-333 Liquid Extraction Detergent May 30, 2017 46-85B S825

Manufacturer:

Canadian Contact:

Legend Brands 325 S. Price Rd. Chandler, AZ 85224 Phone: 480-899-7000 Fax: 480-786-9538 Email: info@prochem.com www.prochem.com Legend Brands 4520 Eastgate Parkway Mississauga, ON L4W 3W6 Phone: 800-932-3030

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Acute toxicity, 5 Oral

Health, Skin corrosion/irritation, 3

Health, Serious Eye Damage/Eye Irritation, 2 B

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:

No GHS pictograms indicated for this product

GHS Hazard Statements:

- H303 May be harmful if swallowed
- H316 Causes mild skin irritation
- H320 Causes eye irritation

GHS Precautionary Statements:

P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P337+313 - If eye irritation persists: Get medical advice/attention.

Route of Entry:	Eyes; Skin; Inhalation;
Target Organs:	Eyes; Skin;
Inhalation:	Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact:	May cause irritation.
Eye Contact:	May cause irritation.
Ingestion:	Ingestion is not applicable route of entry for intended use.

Safety Data Sheet SDS




XL-333 Liquid Extraction Detergent

SDS Number: S825

Revision Date: May 30, 2017

Page 2 of 5

NFPA: Health = 2. Fire = 1. Reactivity = 0. Specific Hazard = n/a HMIS III: Health = 2, Fire = 1, Physical Hazard = 0 HMIS PPE: B - Safety Glasses, Gloves



COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

3

Cas#	%	Chemical Name
111-76-2	5%	Ethylene glycol monobutyl ether
6834-92-0	1%	Sodium metasilicate
497-19-8	3%	Sodium Carbonate
141-43-5	2%	Monoethanolamine

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention. Wash with soap and water. If irritation persists consult medical personnel. Skin Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate Eye Contact: irrigation. Get immediate medical attention. Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

FIRE FIGHTING MEASURES

100°C/ 212°F Flash Point Method:

Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6

5

Flash Point:

ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.



SDS Number: S825



XL-333	Liquid	Extraction	Detergent
--------	--------	------------	-----------

Revision Date: May 30, 2017

Page 3 of 5

7	HANDLING AND STORAGE
Handling Precautions:	Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.
Storage Requirements:	
8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	Normal room ventilation is satisfactory for limited use

 Engineering Controls:
 Normal room ventilation is satisfactory for limited use.

 Personal Protective
 HMIS PP, B | Safety glasses, Gloves

 Equipment:
 Participation

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

9 PHYSICAL AND CHEMICAL PROPERTIES **Appearance:** Clear olive green Odor: **Physical State:** Liquid Citrus Spec Grav./Density: 9.05 lb/gal Solubility: Soluble 11.9 - 12.6 as is / 9.6 - 9.9 RTU pH: 10 STABILITY AND REACTIVITY - 4 - 1- 1 - -. . . .

Hazardous Polymerization:	Will not occur.
Hazardous Decomposition:	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Materials to Avoid:	None known
Conditions to Avoid:	None known
Chemical Stability:	Product is stable under normal conditions.

Toxicity Data:

11

Ethylene glycol butyl ether 111-76-2

Oral (LD 50): 917 mg/kg - Rat

Inhalation (LC 50): 2900 mg/m3/7H - Rat

Skin irritation: Mild

Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

Sodium Metasilicate 6834-92-0

Oral (LD 50): 1153 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

SDS

SDS Number: S825



XL-333 Liquid Extraction Detergent

Revision Date: May 30, 2017

Page 4 of 5

Sensitation: Not considered an occupational sensitizer

Sodium Carbonate 497-19-8

Oral (LD 50): 4090 mg/kg - Rat

Inhalation (LC 50): 2300 mg/m3/2H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Moderate - Rabbit

Sensitation: Not considered an occupational sensitizer

Monoethanolamine 141-43-5

Oral (LD 50): 1720 mg/kg - Rat

Inhalation (LC): 1750 mg/kg - Rat

Skin irritation: Moderate - Rabbit

Eye irritation: Severe - Rabbit

Sensitation: Not considered an occupational sensitizer

12 ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13 DISPOSAL CONSIDERATIONS

Recommendation: Consult with the disposal agency and the relevant authorities. Empty containers may be cleaned with water.

14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

Safety Data Sheet



XL-333 Liquid Extraction Detergent

Revision Date: May 30, 2017

Page 5 of 5

SDS Number: S825

15

SDS

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Ethylene glycol monobutyl ether (111762 5%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Sodium metasilicate (6834920 1%) TSCA, WHMIS

*Sodium Carbonate (497198 3%) TSCA, WHMIS

*Monoethanolamine (141435 2%) HAP, MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

HAP = Hazardous Air Pollutants MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level WHMIS = Workplace Haz Mat Info Sys Canada

16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000